## Low Pressure Measurement Kit 5300 Series



Quick Start Guide

P/N 6011710, Rev. C June 2023

# 5300 Series Low Pressure Measurement Kit (5300-LPMK) Components

Item	Description	Qty.	Picture
1	22-mm (M/F) Airway Pressure Fitting with Screen	2	
2	1/8 inch ID x 1/4 inch OD Tubing	96 in.	

#### **Assembly**

Standard Setup: 22-mm ISO Tube Ends

 Attach the 22-mm Airway Pressure Fitting to the outlet side Tube End of the 5300 Series Instrument with the barb facing up.

 Measure and cut a length of tubing and connect it from the Airway Pressure Fitting barb to the (+) port on the Multi-Meter.



#### **Assembly**

Alternative Setup: 15 mm, 3/4 inch or 1/2 inch Tube Ends

 Remove tube ends from the meter then screw the collars back on.


Insert the Airway Pressure Fitting into the outlet side of the Multi-Meter in the inverted direction with the barb facing up.



- Measure and cut a length of 1/8 ID x 1/4 OD tubing and connect it from the Airway Pressure Fitting barb to the (+) port of the Meter.
- Insert the Inlet Filter–Low Pressure (supplied in Std Accessory Kit) into the inlet side of the Multi-Meter in the inverted direction.



5. Insert alternative Tube Ends into the inlet of the Filter and into the outlet side of the Airway Pressure Fitting.





### Knowledge Beyond Measure.

for more information

TSI Incorporated - Visit our website www.tsi.com

USA Tel: +1 800 680 1220 IJК France

Tel: +44 149 4 459200 Tel: +33 1 41 19 21 99 Tel: +49 241 523030

TSI and TSI logo are registered trademarks of TSI Incorporated in the United States and may be protected under other country's trademark registrations.

> Tel: +91 80 67877200 Tel: +86 10 8219 7688 Tel: +65 6595 6388

Printed in U.S.A.

P/N 6011710 Rev C

Germany

©2023 TSI Incorporated

India

China

Singapore