

VAPex

Low Flow Air Sampling Pump

The VAPex range has been designed particularly for low flow sampling of vapours and gases in working environments. Its Instrinsically Safe design and remote operation via the Airwave App makes it ideal for modern day sampling requirements.

Join us in working today for a healthier tomorrow.

CASELLAS

www.casellasolutions.com



Key Features

- Intrinsically Safe
- Wide low flow range 20mL 500mL/min
- Wireless Bluetooth connectivity
- Remote Start/Stop from Airwave App
- IECEx and ATEX certified EX ia IIC T4 Ga
- Pocket size form factor
- Remote calibration
- Motion sensing technology
- Auto restart function
- Simple and smooth (Noise Free) operation
- Rapid charging of battery
- Add sampling notes on the go

Simple Operation

Casella products are known in the industry for their ease of use and the VAPex is no exception to this. Using only four buttons you can easily navigate through the color coded setup menus.

- Just tap a key to start a run
- Displays battery life in remaining hours as well as flow rate
- Intuitive color display to show device status
- Status LEDs showing pump state from a distance



Easy to use menu



Color coded display showing remaining battery life

Use Airwave on your mobile device to remotely monitor multiple pumps, without disturbing the wearer!



s o s ≈ ∕AirwaveCAS	* .al 504 12:03	so o s≋ ∕ArvaveCASEL	∦ "л] 692.≜ 12:04 ЦАХЕ мени	SAMSUNG SAMSUNG Arwave CASELLA Vapex (3874416	■ 50% ■ 12:04 ■ MEMU		50% 12:04 Menu	Airwaye CA	* 12€:912 = 12.05 SELLA∵ Е мани
Vape: S/N: 999	9099	O ^{Vapex(3874)}	8	RUN DATA Flow Rate Volume Sampled	200mL/m 0.86L	Vapex(3874416)		() Vapex(Send Results via eMail Copy to Clipboard
	tion: 00:06:01	Status	STOPPED	Inlet Pressure Motion Index	0.0kPa	RUN DATA		Status	Settings
Flow Rate Volume S	Sampled 1.203 L	Battery Charge	99%	Blockage Restarts	0	Flow Rate	200mL/m	Battery Charge	About
Motion In Flow Fau	ndex 0%	Memory Free	79%	Temperature	27°C	Volume Sampled	0.86L	Memory Free	A0301
Battery (1		Start Time 20	015-00-04,10:09:14	Battery Hours Remaining	33:28	Inlet Pressure	0.0kPa	Start Time	2015-00-04,10:13:51
		Run Duration	00:03:52	())())		Motion Index	0%	Run Duration	00:04:47
Vape: S/N: 387		RUN DATA				Blockage Restarts	0	RUN DATA	
Run Dura	tion: 00:00:08	Flow Rate	200mL/m			Temperature	27°C	Flow Rate	199mL/m
Flow Rate		Volume Sampled	0.77L			Battery Hours Remaining	33:28	Volume Sampled	1 D.95L
Volume S Iniet Pres Motion In Flow Fau Battery (I	ssure 0.0 cmH20 ndex 0 % its 0								
	1	2		COSE	ex d	3			4
Find vo	our VAPex	Click '	Run'			Start viewi	na	Emoi	-
	Airwave	Butt					•		l a copy of
0117	AII WAVE	Bull	011		3	the sampli	•	-	on the go



Designed for Supreme Performance

VAPex pumps have been designed to give optimum performance for low flow rate applications. Its highly sophisticated control mechanism allows users to collect samples at extremely low flow rates to capture vapors and gases via sorbent tubes.

- Run time of 34 hours at optimum use
- Flexibility to work with all tubes and kits
- Outstanding back pressure capability
- Excellent flow control and stability

VAPex has an outstanding back pressure capability to ensure uninterrupted smooth operation of the pump even in the most demanding settings. Innovative technology embedded in VAPex provides unique features to the user.

"We wanted to have a dedicated low flow pump for gases, one we could use without any low flow adaptor"

Intelligent and Easy to Wear Design

VAPex has one of the most practical, slim and lightweight cases designed with user convenience in mind. The wearing clip comes with a lifetime guarantee.

- Display with highly visible color coded menus
- Motion sensor to ensure compliance and operation
- Ergonomically designed case weighing only 220 grams
- Recessed inlet spigot to prevent damage
- Large buttons with lockable keypad



Bluetooth Connectivity

Monitor your VAPex remotely with Bluetooth[®] and the supporting Airwave App on your phone or tablet.


- Monitor the pump without disturbing the wearer
- Monitor multiple pumps
- Start and stop pumps remotely
- Email data direct to your PC

Intrinsically Safe

VAPex is an Intrinsically Safe (IECEx) pump for use in potentially hazardous atmospheres. Although VAPex is ideal for use in oil and gas, pharmaceutical and chemical industries. Its applications are also frequent where occupational health and safety is in question.

Ex ia IIC T4 Ga (Ta = -20°C to +45°C)

Data Storage and Analysis




The VAPex can store up to 200 separate runs, storing data including start time, stop time, date, duration, volume sampled and motion index.

- Simple to use download utility for PCs
- Graphs flow, motion and back pressure
- Shows events such as blockages
- Downloads into Excel to easily view and share data

Technical Specification Flow Performance

Flow Range ml/min: Flow Control: Back Pressure: Run Time: 20-500 < ± 5% at setpoint 70cm @ 500mL/min 34 hours at 200mL/min (20cm H₂O Back Pressure)

Back Pressure vs Battery Life



Physical

Dimensions:	
Weight:	
IP Rating:	

3.4 x 3.2 x 1.8 (LWD) inches 7.76oz IP65

Environmental

Temperature:41°F - 113°FBarometric Pressure:Auto-correcting

Electrical

Battery Type:High capacity Li-ion batteryChargers:Single or 5-way dock, <6hrs charge time</td>

Model Selection

VAPex	Standard	Pro
Intrinsically Safe	•	•
Motion Sensor	•	•
Constant Pressure Mode	•	•
Bluetooth		٠
PC Download		٠
Run Duration Timer		٠
Fully Programmable Timers		•
Logging of Flow and Motion		٠



Casella US, Shoreview, USATel:+1-800-366-2966Email:info-us@casellasolutions.com

Casella UK, Bedford, United KingdomTel:+44 (0) 1234 844100Email:info@casellasolutions.com

Ordering Information

VAPEX	VAPex I.S Standard Pump
VAPEXPRO	VAPex I.S Pro Pump

All pumps include 1m tube, Field Guide and a Certificate of Calibration and Conformity.

214020B/KIT	Single Docking Station for VAPex inc PSU & USB Cable
214024C/KIT	5-Way Docking Station for VAPex inc PSU & USB Cable
VAPEX/KIT	5-Way VAPex Standard Kit with tubing, docking station, PSU with universal connections and USB cable
VAPEXPRO/KIT	5-Way VAPex Pro Kit with tubing, docking station, PSU with universal connections and USB cable

VAPex pump with 5-way charger



Related Products

Connect the VAPex with our Flow Detective to run seamless calibration through your Airwave App.



Distributed By:

Casella reserves the right to amend the specification without notice