


Product Guide





Building strong health and safety programs together

As an occupational health & safety professional or an industrial hygienist, you are continuously auditing, documenting, and taking corrective or preventive actions. It's the only way to keep your teams safe and healthy—and to stay in compliance.

A strong safety program depends on good data. Only with correct measurements, can you identify risks, report on them with confidence, and make informed decisions.

Measuring What's Important

TSI® develops and manufactures accurate and reliable occupational health and safety instruments to measure what's important in your safety program. We understand how important your job is—and what you need to do it well.

Trust TSI° to help you handle your OH&S challenges every day.

Respirator Fit Testers

PortaCount™ Respirator Fit Tester

Models 8040 & 8048

The PortaCount™ Respirator Fit Tester provides a consistent and objective HSE INDG 479 and ISO 16975-3:2017 respirator fit test. Beyond the fit test, PortaCount™ instruments allow users to see how respirator fit changes in real-time during donning and adjustment, providing valuable training and making mask selection easy.

The PortaCount Respirator Fit Tester Model 8048 can fit test any respirator, including all disposable masks. The model 8040 provides the same quality fit test for all respirators with ≥99% filter efficiency.



Tablet is sold separately or with the 8040-TUK/8040-TEU or 8048-1-TUK/8048-1-TEU packages.





- Quantitative respirator fit testing (QNFT)
- Half-facepiece elastomeric respirator fit testing
- Full-facepiece elastomeric respirator fit testing
- Disposable filtering-facepiece respirator fit testing for NIOSH Series -95 / -99 / -100 and FFP1/FFP2/FFP3 masks (availability dependent on model)
- SCBA fit testing

Exposure Monitoring

Aerosol Monitors

DustTrak[™] II and DustTrak[™] DRX Aerosol Monitors

Models 8530 & 8533

The DustTrak™ II and DustTrak™ DRX Aerosol Monitors are battery-operated, data-logging, light-scattering laser photometers that provide real-time mass concentration readings for aerosol contaminants such as dust, smoke, fumes and mist. Instruments use a sheath air system that isolates the aerosol in the optics chamber to keep the optics clean for improved reliability and low maintenance.



The DustTrak™ II Aerosol Monitor provides real-time aerosol mass readings, while the DustTrak™ DRX Aerosol Monitor can measure mass concentrations in four size fractions simultaneously. Both instruments also collect gravimetric samples for lab analysis.

- Industrial/occupational hygiene surveys
- Outdoor environmental monitoring
- Engineering control evaluations
- Process monitoring
- Aerosol research studies



Handheld Aerosol Monitors

DustTrak[™] II and DustTrak[™] DRX Handheld Aerosol Monitors

Models 8532 & 8534

The DustTrak™ II Aerosol Monitor 8532 is a handheld battery-operated, data-logging, single-channel, light-scattering laser photometer that gives you real-time aerosol mass readings. It uses a sheath air system that isolates the aerosol in the optics chamber to keep the optics clean for improved reliability and low maintenance.

The DustTrak™ DRX Aerosol Monitor 8534 uses the same technology as the 8532 while adding multi-channel capabilities that can simultaneously measure both mass and size fraction.



Applications Industrial/occupational hygiene surveys Indoor air quality investigations Point source location monitoring Baseline trending and screening Engineering control evaluations

Personal Aerosol Monitors SidePak™ Personal Aerosol Monitors Models AM520 & AM520i

SidePak™ AM520 and AM520i Personal Aerosol Monitors measure worker exposure to respirable dust, silica and diesel particulate matter (DPM), including: PM10, PM4 (respirable), PM2.5, PM1, and 0.8µm DPM. Designed to take measurements from the worker-breathing zone, they are the industry's most versatile, lightweight personal aerosol monitors.



The SidePak™ AM520i is IECEx, ATEX, CSA, and IECEx-SIM certified for use in explosive environments.

Industry Applications

- Respirable silica
- Welding
- Bulk material handling
- Chemical manufacturing and processing
- Mining
- Oil and gas /petrochemical

Primary Calibrator Models 4046 & 4146

TSI® offers the Model 4046 and Model 4146 Primary Calibrators used to calibrate the flow rate of air sampling instruments. These portable, battery-operated units are easy to operate and come with +/- 2 % of reading accuracy. Volumetric flow rate is displayed continuously so adjustments to pump flow can be made in real-time.





Noise Monitors Quest™ Edge Personal Noise Dosimeters Models 7 & 8

QuestTM Edge Personal Noise Dosimeters are the perfect blend of flexibility and reliability for measuring and data logging a worker's personal noise exposure. This assists safety professionals with compliance in hearing conservation programs.

They're a powerful and intuitive instrument with countless capabilities that provide accurate data on noise exposure levels. Designed for day-after-day use and tough environments with intuitive detection management software that offers a variety of flexible functionality makes it a powerhouse.

Quest™ Edge 7 Personal Noise Dosimeter available now in the US and Canada. Coming soon to additional countries.

Quest™ Edge 8 Personal Noise Dosimeter - available as soon as the final regulatory certifications are received. Intrinsically safe - designed to be used in potentially hazardous environments.

- Mining (Edge 8 for underground)
- Oil & gas, and energy
- Manufacturing
- Noise consultancy
- Government and military



Sound Level Meters Quest™ Sound Examiner and SoundPro™ Sound Level Meters SE-400 & SP-Series

Quest™ Sound Level Meters make it simple to documentand analyze sound levels across variable environments.

- Designed with industrial hygienists in mind, Sound Examiner instruments are ideal for managing hearing conservation programs.
 The IECex and ATEX intrinsically safe certified option is ideal for oil and gas applications.
- SoundPro[™] Sound Level Meters add octave band analysis, offering comprehensive sound data information for industrial hygienists, engineers, and audiologists.



Applications

- Occupational noise evaluations
- Environmental noise assessments
- General sound and frequency analysis
- Noise violations and community noise monitoring
- Automotive design and vehicle noise evaluations

Acoustic Calibrator Model AC-300

The AC-300 Acoustic Calibrator with class 1 microphone calibrates all Quest™ Noise Dosimeters and Sound Level Meters. The microphone produces two signals: 250 Hz or 1,000 Hz at a sound pressure level of 114 dB.

Heat Stress Monitors QuestTemp° WBGT Heat Stress Monitors Models 32/34/36 & 44/46

QUESTemp° Heat Stress Monitors are designed to quickly and accurately evaluate potential heat stress environments.

- The QUESTemp° 44/46 models utilize a waterless wet bulb sensor to calculate wet bulb globe temperature (WBGT).
- It eliminates the need for daily wet bulb upkeep.
- The QUESTemp° 32/34/36 models utilize a traditional wet bulb for the calculation of a WBGT index value.

Visit the TSI® website for more information on model features.



- Environmental remediation
- Military and government
- Energy and utilities
- Manufacturing





TSI Link™ Solutions

TSI offers a full air monitoring solution that includes IoT devices such as AirAssureTM IAQ monitors and BlueSkyTM outdoor air quality monitor in combination with TSI LinkTM software.

TSI Link™ is the cloud-based platform that allows you to manage devices and view air quality data from anywhere at any time, while providing also multiple integration opportunities through API.

Benefits of TSI Link Solutions & API Data Services:

- Remote Device Management
- Customizable Dashboard and Real-Time Alerts
- Seamless Integration with BMS, Third-Party Software and Analytics Tools
- Ability to Send Data to Customer's Own Platform



Applications


- Indoor Air Quality monitoring
- Wildfire/External pollutant- Air Monitoring for employee protection
- Help improving energy efficiency
- Assess building filtration and ventilation efficacy
- Construction project monitoring
- Long term data monitoring and research

For more information, please visit tsi.com/tsilink



TSI Link™ IoT Platform

A Flexible Solution for Your Customized Needs



Air Quality Monitoring

Continuous IAQ Monitors AirAssure™ Indoor Air Quality MonitorsModels 8144-6, 8144-4, 8144-2

The TSI AirAssure™ Indoor Air Quality Monitors available in two, four, and six-gas models are designed to help you optimize your indoor air quality ventilation needs, while helping to achieve a safe and productive space. Utilizing low-cost sensor technology to continuously monitor gas and particulate pollutants along with essential IAQ parameters to help you achieve ideal indoor air quality. The device is able to measure the level of CO, CO₂, Formaldehyde, tVOCs, SO₂, O₃, NO₂, as well as particulate matter (PM), barometric pressure, temperature and relative humidity.





- Schools, colleges & universities
- Childcare & youth programs
- Government agencies and environmental organizations
- Healthcare, hospitals, assisted living campuses, and medical office buildings
- Industrial manufacturing, factories, power generation and petrochemical plants
- Hotels, conference centers, shopping malls, athletic/entertainment arenas
- Researchers and Community Groups looking to collect IAQ data



Environmental Air Quality Monitoring BlueSky[™] **Monitors**Models 8143, 8145

Available in two models to meet your needs, BlueSky™ Environmental Air Quality Monitors are small, lightweight, and affordable. Designed for easy installation, you can operate each monitor individually or as a network of sensors using more than one, accurately reporting real-time, localized air quality measurement data through TSI Link™ Software Solutions.

While specifically designed for outdoor environmental monitoring, BlueSky Air Quality Monitors can also be utilized inside buildings, homes and manufacturing facilities to measure indoor air quality.



BlueSky	8143	8145
Particulate Matter (PM 1.0)	0140	0140
Particulate Matter (PM 2.5)		
Particulate Matter (PM 4.0)	•	
Particulate Matter (PM 10)		-
Ozone (O ₃)		•
Nitrogen Dioxide (NO ₂)		-
Sulfur Dioxide (SO ₂)		•
Carbon Monoxide (CO)		-
Carbon Dioxide (CO ₂)		-
Barometric Pressure (BP)		-
Temperature	-	-
Relative Humidity (RH)	-	-

- Air Quality Monitoring for Respiratory Health
- Fenceline/Perimeter Monitoring
- Municipalities & Smart Cities
- Community Monitoring **Programs**
- Hot Spot Detection
- Indicative Comparisons to Federal Reference Air **Quality Data**



Outdoor Environmental Monitors DustTrak™ Environmental Monitors

DustTrak™ Environmental Monitors are approved MCERTS air monitoring systems utilizing datalogging, light-scattering laser photometers. Early detection features on the DustTrak™ allow for a quick response to exposure concerns. This system is built upon proven technology that thousands of people use every day.

There are a number of model configurations available for the DustTrak Environmental Monitor System.

Visit the TSI® website for more information.

- Outdoor environmental monitoring
- Monitoring for a Community Air Monitoring Plan (CAMP)
- Brownfields/remediation monitoring
- Fence-line construction monitoring





Multi-Function Ventilation Meters

VelociCalc™ 9600 Series

Models 9600, 9630, 9650, 9650NB

The VelociCalc™ Multi-Function Ventilation Meter 9600 series includes a built-in workflow for calculating the percentage of outside air used to determine ventilation effectiveness in a building or room.

The VelociCalc™ Pro adds built-in workflows for heat flow calculation and four methodologies for performing a duct traverse. It's ergonomic design includes a probe holder and integrated magnets allowing for attachment to exposed ductwork, chemical fume hoods and biological safety cabinet frames hands-free operation. These instruments are available with or without a differential pressure sensor, and are designed to work with a wide range of plug-in probes.





Indoor Air Quality Monitors Q-Trak™ XP Indoor Air Quality Monitors

Model 7585

This product is only available in North America.

Providing a comfortable, safe, and healthy indoor environment is an increasingly important concern. Good indoor air quality improves concentration and productivity and can also reduce lost days due to health-related absences.



Applications

IAQ surveys and investigations

 Proactive IAQ monitoring (schools and office buildings)

 Indoor air quality compliance testing to local or regional standards and guidelines

 Evaluating thermal comfort (temperature and relative humidity)



Ultra Fine Particle Counters P-Trak™ Ultra Fine Particle Counters Model 8525

The P-TrakTM Model 8525 Ultrafine Particle Counter gives direct, real-time measurement of workplace ultrafine particulate levels (smaller than 1 μm). This portable instrument detects and counts ultrafine particles that often accompany or signal the presence of a pollutant that can be the root cause of IAQ complaints.



- Check office equipment
- Off-gassing of chemical cleaning agents
- Vehicle emission migration
- Combustion leaks



QualityGuard[™] Service & Calibration Agreements

TSI° instruments set the standard for reliability and accuracy. Protect your investment now and in the future with a TSI° QualityGuard™ Calibration or Bumper-to Bumper (B2B) Warranty Contract.

Why Do I Need a TSI° Service Contract?

- Upfront Fixed Costs. No need to procure additional funding for annual calibration and repairs.
- **Optimal Performance.** Regular service and calibration is the best way to ensure optimal performance during critical projects.
- Instrument and Firmware Updates. Improvements are implemented to products on an on-going basis, some of which are available to customers at no additional charge when their instruments are returned for annual maintenance and calibration.
- Quality. Our Quality System is registered to ISO 9001:2015, and TSI uses NIST traceable analytical tools and NIST traceable standard reference materials to check out and calibrate instruments.
- Technical Expertise. TSI has invested in sophisticated instrumentation to allow our experienced service technicians to test, calibrate and repair our instruments with unparalleled precision.
- Value. QualityGuard™ Calibration and B2B Warranty Contracts are priced to be an incentive for routine calibration and extended warranty services.

To learn more and find out if your instrument qualifies visit: tsi.com/support/service-and-calibration-agreements



Experts You Can Trust

TSI® expert technicians know how to best take care of your equipment and are trained to test, calibrate, adjust and repair your instruments with unparalleled precision.

While third-party labs can only verify your instrument, TSI® can perform multipoint calibration and adjustment, update software, firmware and repair with original parts – all from certified factory-trained technicians. Whether you are looking for calibration or repair, **TSI** is the one-stop solution for your service needs.


At Your Service Worldwide, with Local Support

Enjoy excellent services with reduced turnaround time through TSI regional centers around the globe.

- O Shoreview, MN | US
- Q High Wycombe | UK
- Aachen | Germany
- O Beijing | China
- O Singapore | Singapore
- O Gyeonggi-do | Republic of Korea



No one knows more about your instrument than the manufacturer



OPERATING AT A GLOBAL AND HUMAN SCALE

Around the globe, TSI* provides a comprehensive range of solutions with unparalleled reliability and accuracy necessary to accomplish your goals. From workflow management, software services and measurement instruments, our complete suite of solutions are tailored to help you make informed, data-driven decisions to get your job done. Turning data into actionable information enables you to do your job more efficiently. TSI* understands the science, the data, and the processes that support your work.

We are proud to provide you with a wide array of solutions to help you with your Occupational Health & Safety concerns. Our local Sales Representatives are close by, ready to assist you.

To learn more, visit tsi.com

TSI® are registered trademarks of TSI Incorporated in the United States and may be protected under other country's trademark registrations.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by TSI Incorporated is under license. Other trademarks and trade names are those of their respective owners.



TSI Incorporated - Visit our website www.tsi.com for more information.

 USA
 Tel: +1 800 874 2811
 India
 Tel: +91 80 67877200

 UK
 Tel: +44 149 4 459200
 China
 Tel: +86 10 8219 7688

 France
 Tel: +33 1 41 19 21 99
 Singapore
 Tel: +65 6595 6388

 Germany
 Tel: +49 241 523030

P/N 5002621 Rev C ©2023 TSI Incorporated Printed in U.S.A. 5147038926