



Knowledge Beyond Measure.

PortaCount™ Respirator Fit Tester

Models 8040 / 8040-T



Tablet included
with 8040-T kit

Respirator Fit Testing You Can Trust.

The *PortaCount*™ Respirator Fit Tester Models 8040 and 8040-T provide a consistent and objective quantitative respirator fit testing experience for all respirator face masks using $\geq 99\%$ efficient filter media. Industry-first features train staff how respirators should be worn to be most protective.

Choose *PortaCount*™ Fit Testers for respirator training and fit testing you can trust.

Features and Benefits

- OSHA, CSA, HSE INDG, ANSI/ASTM, ISO, INRS and JIS accepted for ALL Full-facepiece and Half-facepiece tight fitting elastomeric respirators and filtering facepiece respirators, using NIOSH Series -99 /-100; EN-P3 filter media
- Measures fit factors from 1 to greater than 10,000
- Computes respirator fit factor using microscopic particles in ambient air
- Automates fit testing with *FitPro*™ Ultra Software
- Real-Time *FitCheck*™ Mode to train new users and troubleshoot failed fit tests
- Optional mask sampling adapter kits enable fit testing in employee's personal respirators
- *FitPro*™ Ultra Software can print fit test cards with fit test report

PortaCount™ Models 8040/8040-T include:

- Carrying case
- AC power supply with global plug adapters
- Alcohol supply (sixteen 30 ml bottles of 99.5% reagent grade isopropanol – enough for ~240 hours of operation)
- *FitPro*™ Ultra Fit Test Software
- Standard accessory kit (twin tubing, zero filters, spare wicks, alcohol fill capsule and cartridge, USB cable)
- Ruggedized Windows 11 tablet PC with 10.5" LCD screen (included with 8040-T kit)

FitPro™ Ultra Software

- New *FitPro*™ Ultra Fit Test Software improves efficiency and simplifies fit testing
- New advanced user interface with designed for efficiency with intuitive workflows providing one-step-to-a-fit test
- Wireless WiFi® communication to leverage the utility of a laptop or tablet
- Industry first active animations guide the test subject through the fit test exercises to help ensure better worker protection, not just compliance, improving fit test success rate for confidence and greater productivity
- Interactive user guides



Specifications

PortaCount™ Respirator Fit Tester

Models 8040/8040-T

Fit Factor Range

1 to greater than 10,000

Respirator Facepieces that can be Fit Tested

Full-facepiece elastomeric
Half-facepiece elastomeric
NIOSH Series-100 filtering-facepiece
NIOSH Series-99 filtering-facepiece
EN FFP3 filtering-facepiece

Fit Factor Measurement

Direct measurement of fit factor = $(C_{out}/C_{in})^*$

Dimensions

4.83 in. x 10.5 in. x 9.46 in. (12 cm x 27 cm x 24 cm)

Weight

Instrument Only	6.1 lb. (2.7 kg)
With Standard Accessories and Case	14.45 lb. (6.5 kg)

Power

Autosensing 100 to 250 VAC, 50 to 60 Hz

Flow Rate

Sample	350 cm ³ /min
Total	1000 cm ³ /min (nominal)

Temperature Range

Operation	32 to 100° F (0 to 38° C)
Storage	Storage -40 to 122° F (-40 to 50° C)

Working Fluid

99.5% reagent grade isopropanol.

Run time per charge: Typical 6 hr of fit testing operation at 70°F (21°C)

Carrying Case

Dimensions (HWD) 10.0 in. x 20.5 in. x 15.5 in.
(25.4 cm x 52.1 cm x 39.4 cm)

Pass/Fail Setting

User-selectable: 0 to 10,000

Factory Recalibration Interval

One year

Warranty

Two years on workmanship and materials

Communications

WiFi, USB-C, USB-A

PC Hardware Requirements for FitPro™ Ultra Fit Test Software

Windows® 10, and Windows® 11 (64 bit) operating system
Complete install including .Net support
Note — An internet connection is required to install Microsoft .Net
≥ 1 GHz process
≥ 1280 x 800 screen resolution monitor
500 MB free space on hard drive
1 free USB port

Tablet Requirements

Windows 10 and Windows 11 operating system
USB port (for initial set up)

Software

FitPro™ Ultra Fit Test Software featuring advanced user interface, animated graphics, and interactive troubleshooting guide

Optional Accessories

Mask Sampling Adapters for select respirator models

Ruggedized Windows 11 tablet PC

Tablet details: Sunlight Readable 10.5" LCD Screen (1920 x 1280 Resolution), Windows 11 Pro, 2 x USB C Ports, Magnetic Charger Jack / Charging cord, 8GB Memory, 128GB Storage, Intel® Wi-Fi, Bluetooth 5.2, IP66 Water & Dust Protection, Ruggedized design, USB-C (M) to USB-A (F) adapter included, Folding support stand on rear of tablet

To see more specs please visit: <https://tsi.news/4j2KN0>

WiFi USB dongle

*Mask leakage is measured simultaneously while test subject moves and breathes.

Specifications are subject to change without notice.

Wi-Fi is a registered trademark of the Wi-Fi Alliance.

Windows and Microsoft are registered trademarks of Microsoft Corporation in the United States and/or other countries.

FitCheck, PortaCount, TSI and the TSI logo are registered trademarks of TSI Incorporated in the United States and may be protected under other country's trademark registrations.

To see our list of patents please visit:
www.tsi.com/patents



Knowledge Beyond Measure.

TSI Incorporated - Visit our website www.tsi.com for more information.

USA	Tel: +1 800 874 2811	India	Tel: +91 80 67877200
UK	Tel: +44 149 4 459200	China	Tel: +86 10 8219 7688
France	Tel: +33 1 41 19 21 99	Singapore	Tel: +65 6595 6388
Germany	Tel: +49 241 523030		