

FLOW-FOCUSING MONODISPERSE AEROSOL GENERATOR MODEL 1520



The Flow-Focusing Monodisperse Aerosol Generator (FMAG) Model 1520 is an advanced aerosol generator. Successfully generating monodisperse aerosol particles in a matter of minutes, the FMAG produces final particle sizes, from solid materials, at 0.8 - 8.5 μm and up to 12 μm from nonvolatile liquid materials.

Applications

There is a wide variety of compatible liquid and solid materials for the FMAG, (see Compatible Materials section for full list). With this wide range, the FMAG is a valuable tool for numerous applications and can be used for:


- + Generating laboratory standard aerosols for calibrating droplet and aerosol particle sizing instruments such as aerosol spectrometers and cascade impactors
- + Generate known size particles at a known rate for laboratory experimentation and exposure studies
- + Generate viable bioaerosols and proxy biomaterials for bioaerosol research in a variety of sectors

Features and Benefits

- + Generates monodisperse aerosol particles of an accurately known particle diameter
- + Low shear stress, non-clogging design
- + Built-in corona aerosol neutralizer
- + An easy-to-use instrument with advanced touch-screen control and user-friendly features

Compatible Materials

Using this solvent evaporation technique, a variety of solid and liquid materials can be generated by the FMAG. Successful liquid materials include oleic acid, DOP (dioctyl phthalate) and glycerol. Successful solid materials include sodium chloride, ammonium sulfate, sucrose and methylene blue. In addition, to these dissolved materials, suspended materials such as polystyrene latex spheres (PSLs) can be successfully generated as well and compatible solvents include water and methanol.



SPECIFICATIONS

FLOW-FOCUSING MONODISPERSE AEROSOL GENERATOR MODEL 1520

How it Works

The operation of the FMAG is based on proven aerosol generation technology and includes:

1. Stable, mechanical generation of monodisperse droplets: a liquid stream is squeezed through a nozzle, and forms a narrow jet with the coaxial flow-focusing air. This jet is subjected to mechanical vibration, and breaks up into droplets that have the same volume.
2. Conditioning of droplets into particles: once generated, the droplets are dried into particles by exposure to dry dilution airflow. They are also electrically neutralized to optimize the successful transport of the particles from the generator into the intended application. While maintaining these strengths, the FMAG also incorporates a significant step forward from previous technology.

While maintaining these strengths, the FMAG also incorporates a significant step forward from previous technology:

1. Flow-focusing air. Reflected in the name 'FMAG', the use of flow-focusing air allows the instrument to operate with a much larger nozzle (100mm). This significantly reduces clogging and downtime
2. Low shear stress: the low liquid pressure operation is suitable for use with biological aerosols. Cell viability following aerosolization is enhanced when using FMAG, making it a useful tool for a wide variety of bioaerosol applications.
3. NIST-traceable particle size: The FMAG operating parameters are calibrated with NIST traceable standards. This allows users to use the FMAG for instrument calibration applications.
4. Corona aerosol neutralizer: this non-radioactive neutralizer generates a bipolar cloud of gaseous ions to neutralize any electrical charge that may be generated during the droplet and particle formation process. This feature is important in scientific research and laboratory experimentation, since unwanted or uncontrolled particle electric charge can adversely affect the behavior of aerosol particles and compromise the validity of the experimental results.

TO ORDER

HFI Impactors:

Specify Description

1520 Flow-Focusing Monodisperse Aerosol Generator



MSP - Visit our website www.msppcorp.com for more information.

5910 Rice Creek Parkway, Suite 300
Shoreview, Minnesota
55126, U.S.A.
Tel: 651.287.8100

Liquid flow

1 to 24 ml/hr; $\pm 0.50\%$

Vibration frequency

0 to 250 kHz; $\pm 0.1\%$

Droplet diameter*

15 to 90 μm ; $\pm 1.0\%^{***}$

Particle diameter

0.8 to 8.5 (solid) or 12 (liquid) μm^{**} ; $\pm 1.0\%^{***}$

Geometrical standard deviation

< 1.02 for droplets; < 1.05 for liquid/solid particles

Aerosol neutralizer

Bipolar corona (non-radioactive)

Compressed air requirement

30 Std L/min; 100 to 430 kPa (14.5 to 62.5 psig); 0 °C dew point

Dimensions


273 mm x 356 mm x 483 mm (10.7" x 14" x 19") (H x D x W)

Weight

16 kg (35 lb.)

Power requirements

115 or 230 VAC, 50-60 Hz, 50 W max



Specifications are subject to change without notice.

* Droplet diameter accuracy is based on the accuracy of the liquid flow rate and vibrating frequency

** Maximum particle diameter depends on particle density. Larger particles are more difficult to be transported by the flow.

*** Particle diameter accuracy is based upon the accuracy of droplet diameter and solution concentration. (Keep the flowing sentence).

The MSP logo is a registered trademark of MSP Corporation.

TSI and the TSI logo are registered trademarks of TSI Incorporated.