

SMALL-SCALE POWDER DISPERSER MODEL 3433

RUGGED, RELIABLE INSTRUMENTS FOR POWDER
DEAGGLOMERATION AND DISPERSION



TSI's Small-Scale Powder Disperser Model 3433 is used mainly for powder sizing. The operator gently brushes the powder to be dispersed across one of three annular rings of abrasive paper glued to the top of a turntable. One end of a stainless-steel capillary is positioned just above the turntable, the other in a venturi throat. A suction transmitted through the capillary tube removes the powder from the surface of the turntable. Because the air velocity in the venturi throat greatly exceeds that in the capillary tube, shear forces are created where the two flows meet, causing the powder to deagglomerate. The powder then enters an expansion cone, from which it exhausts from the unit.

Applications


- + Generating aerosol for introducing powder into particle sizing systems such as TSI's Aerodynamic Particle Sizer® (APS™) Spectrometer Model 3321
- + Dispersing dry polystyrene latex spheres (PSLs) for use in calibrating measurement instruments
- + Redispersing airborne material collected on 25 and 37 mm diameter membrane filters used in environmental monitoring
- + Inhalation toxicology studies, particularly in the pharmaceutical industry

Features and Benefits

- + Deagglomerates most dry particles in the range from 0.5 to 50 μm
- + Selection of turntables available to meet specific dispersion needs
- + Use as an APS spectrometer accessory for particle-size-distribution measurements



UNDERSTANDING, ACCELERATED



SPECIFICATIONS

SMALL-SCALE POWDER DISPERSER MODEL 3433

Output Concentration Range

0.3 to 4 mg/m³ with standard motor; 3 to 40 mg/m³ with alternate motor

Powder Feed Rate Range

3 to 90 mg/hr

Carrier Gas Flow Rate Range

12 to 21 liters/min at 138 KPa (20 psi)

Particle Size Range

Related to size of powder to be dispersed. Maximum size is approximately 50- μ m aerodynamic diameter; particles smaller than 1 μ m do not deagglomerate efficiently.

Turntable Rotation

Clockwise or counterclockwise, between 0.25 and 3.3 rev/hour; 2.5 to 33.3 rev/hour with optional high-speed motor

Power Requirements

100, 120, 220, 240 VAC; 50 to 60 Hz; 20 W

Dimensions (L x W x H)

386 x 432 x 343 mm (15.2 x 17 x 13.5 in.)

Weight

18 kg (39 lbs)


It is recommended that the powder dispersers described in this brochure be used with the TSI's Air Supply System Model 3074B.

Warning: Dispersed dusts may be toxic and hazardous.

TSI assumes no responsibility for personal injury or property damage due to inappropriate use of these instruments.



Supplied (lower right) and optional turntables.



TO ORDER

Small-Scale Powder Disperser

Specify	Description
3433	Small-Scale Powder Disperser

Optional Accessories

Specify	Description
1030779	Alternate motor to provide 2.5 to 33.3 revolutions per hour
1030737	Additional turntable (127-mm diameter) with three concentric rings of abrasive paper (one is supplied with the instrument)
1030770	Turntable with abrasive rings preloaded with a range (5, 7, 10, 15, 20, and 30 μ m) of monosized dry PSL spheres
1030772	Turntable with three concentric V-shaped grooves
1030771	Turntable with porous plastic membrane filter supports at 25- and 37-mm diameters



UNDERSTANDING, ACCELERATED

TSI Incorporated - Visit our website www.tsi.com for more information.

USA	Tel: +1 800 874 2811	India	Tel: +91 80 67877200
UK	Tel: +44 149 4 459200	China	Tel: +86 10 8251 6588
France	Tel: +33 4 91 11 87 64	Singapore	Tel: +65 6595 6388
Germany	Tel: +49 241 523030		