



® Knowledge Beyond Measure.

# Water-Based Wide-Range Scanning Mobility Particle Sizer™ (SMPS™) for Ambient Air Monitoring

Model 3938W89



## Ultrafine particle monitoring you can count on for years

This particle sizer enables air quality monitoring of ultrafine particles (UFPs) over a wide range of sizes while also using water as a Condensation Particle Counter (CPC) working fluid. The data provided by the Scanning Mobility Particle Sizer™ (SMPS™) can be easily integrated into monitoring networks. A complete solution for monitoring ultrafine particles is available when this SMPS™ system is combined with the sampling system, the humidity sensor, and a software extension specifically designed for ambient monitoring.

### Applications

Designed for continuous air quality monitoring. Thanks to its exchangeable components it can also be adapted to support other support other research goals:

- Air quality monitoring of ultrafine particles
- Environmental chamber studies
- Indoor air quality studies
- Health effect studies
- Basic aerosol research

### Features and Benefits

- Extended particle size range from 10 to 800 nm in a single scan
- New Wide-Range Differential Mobility Analyzer 3083 is based on TROPOS Vienna-type DMA
- Uses distilled water as a CPC working fluid: safe and easily available
- Scan time down to 1 minute: capture dynamic aerosol size distributions (for example, near airports)
- Capable of providing a common log of particle data, relative humidity and temperature when used with the Aerosol Humidity and Temperature Sensor RHT3000



## Specifications

# Water-Based Wide-Range SMPS™ for Ambient Air Monitoring

Model 3938W89

### SMPS™ Settings and Requirements

Aerosol Flow Rate	0.6 or 1.5 L/min
Sheath Flow Rate	2 to 15 L/min, user-selectable
Recommended Minimum Sheath: Aerosol Ratio	5 : 1
Particle Size Range	10 to 800 nm
Measurement Time	1 to 10 minutes, user-selectable
Working Fluid for CPC	distilled water

Particle concentration range: up to 10<sup>7</sup> particles/cm<sup>3</sup>.

Particle resolution: Measured at 128 channels/decade. Ability to adjust resolution to 64, 32, 16, 8 or 4 channels per decade for display and data export. Number of total size channels varies by configuration and settings.

At standard settings (64 channels/decade, 10 to 800 nm scan range, 5 : 1 sheath : aerosol ratio), scan includes 122 channels.

DMA voltage: Standard configuration is negative high voltage on DMA center electrode. An Electrostatic Classifier 308202 is optionally available for dual polarity. For a classifier containing only positive polarity, please contact TSI®.

### Ambient Operating Conditions

Temperature	10 to 35°C
Pressure	75 to 105 kPa
Humidity	0 to 90%, non-condensing

Temperature and pressure affect the available particle size range.

### Data Acquisition

Continuous with PC-based software. The optional monitoring module allows automatic export of multiple data sets (raw and final concentrations), auto-recovery after power outage, and correction of data for particle losses occurring within the sampling system.

### Aerosol Neutralizer Options - Ordered Separately

3077A	370 MBq (10 mCi), Kr-85, Half-life of 10.8-year
3088	Soft X-ray <9.5 keV ~8,760 operating hours
6005931	Lead shielding column for 3077/3077A placed inside 3082 classifier

### Accessories

3750200	Sampling System for Atmospheric Aerosol
RHT3000	Aerosol Humidity & Temperature Sensor
AIM11SMPSMONTRIAL	SMPS™ Monitoring Software Trial: permits current TSI® customers already using AIM 11 to temporarily access Monitoring-specific software features
AIMSMPSMONITOR	SMPS™ Monitoring Software

### Communication & User Interfaces

Ethernet to communicate with monitoring software: 8-wire RJ-45 jack, 10/100 BASE-T, TCP/IP). Configurable for automated (DHCP) or manual network settings.

RS-232 connecting CPC to Classifier

Embedded touch display for local diagnostics

### Power Requirements

3789	200 W
3082	200 W

### Dimensions (H x W x D/Weight)

3082	40 × 28 × 40 cm / 14.2 kg
3083	47 × 13.2 × 15.9 cm / 8.5 kg
3789	30.7 × 18.3 × 40.4 cm / 8.2 kg*
Assembled 3938W89 SMPS system	70.7 × 40.5 × 40.4 cm / 30.9 kg**

\* Without the fill and drain bottles attached

\*\* These dimensions apply to a setup where the 3789 is located atop the Electrostatic Classifier 3082.

Refer to separate product sheets for descriptions and specifications of individual components.

### To Order

Specify	Description
3938W89	SMPS™ for Ultrafine Particle Monitoring; Water-Based CPC
3077A	370 MBq (10 mCi), Kr-85, Half-life of 10.8-year
3088	Soft X-ray <9.5 keV~8,760 operating hours
6005931	Lead shielding column for 3077/3077A; placed inside 3082 classifier
3750200	Sampling System for Atmospheric Particles
RHT3000	Aerosol Humidity and Temperature Sensor
AIM11SMPSMONITOR	Aerosol Instrument Manager SMPS software, monitoring version
3789-MKIT	Maintenance Kit for WCPC
3789-WKIT	Wick Replacement Kit for WCPC



Knowledge Beyond Measure.

TSI Incorporated - Visit our website [www.tsi.com](http://www.tsi.com) for more information.

<b>USA</b>	Tel: +1 800 874 2811	<b>India</b>	Tel: +91 80 67877200
<b>UK</b>	Tel: +44 149 4 459200	<b>China</b>	Tel: +86 10 8219 7688
<b>France</b>	Tel: +33 1 41 19 21 99	<b>Singapore</b>	Tel: +65 6595 6388
<b>Germany</b>	Tel: +49 241 523030		

Specifications are subject to change without notice.

TSI and the TSI logo are registered trademarks of TSI Incorporated in the United States and may be protected under other country's trademark registrations.